

Templates and Polymorphism

Generic functions and classes

JPC and JWD © 2002 McGraw-Hill, Inc.

Polymorphic Functions

- ◆ What are they?
 - Generic functions that can act upon objects of different types
 - ◆ The action taken depends upon the types of the objects

- ◆ Where have we seen them before?
 - Function overloading
 - ◆ Define functions or operators with the same name
 - Rational addition operator +
 - Function Min() for the various numeric types
 - ◆ Primitive polymorphism


Polymorphic Functions

- ◆ Templates
 - Generate a function or class at compile time
- ◆ Where have we seen them before?
 - Standard Template Library
 - ◆ Vector and other container classes
- ◆ True polymorphism
 - Choice of which function to execute is made during run time
 - ◆ C++ uses *virtual* functions

Function Templates

- ◆ Current scenario
 - We rewrite functions `Min()`, `Max()`, and `InsertionSort()` for many different types
 - There has to be a better way
- ◆ Function template
 - Describes a function format that when instantiated with particulars generates a function definition
 - ◆ Write once, use multiple times

An Example Function Template



Min Template

◆ Code segment

```
int Input1 = PromptAndRead();
int Input2 = PromptAndRead();
cout << Min(Input1, Input2) << endl;
```

◆ Causes the following function to be generated from our template

```
int Min(const int &a, const int &b) {
  if (a < b)
    return a;
  else
    return b;
}
```

Min Template

- ◆ Code segment

```
double Value1 = 4.30;  
double Value2 = 19.54;  
cout << Min(Value1, Value2) << endl;
```

- ◆ Causes the following function to be generated from our template

```
double Min(const double &a, const double &b) {  
    if (a < b)  
        return a;  
    else  
        return b;  
}
```

Min Template

- ◆ Code segment

```
Rational r(6,21);  
Rational s(11,29);  
cout << Min(r, s) << endl;
```

- ◆ Causes the following function to be generated from our template

```
Rational Min(const Rational &a, const Rational &b) {  
    if (a < b)  
        return a;  
    else  
        return b;  
}
```

← Operator < needs to be defined for
for the actual template parameter
type. If < is not defined, then a
compile-time error occurs

Function Templates Facts

- ◆ Location in program files
 - In current compilers
 - ◆ Template definitions are part of header files

- ◆ Possible template instantiation failure scenario

```
cout << min(7, 3.14);    // different parameter
                          // types
```

Generic Sorting

```
template <class T>
void InsertionSort(T A[], int n) {
    for (int i = 1; i < n; ++i) {
        if (A[i] < A[i-1]) {
            T val = A[i];
            int j = i;
            do { A[j] = A[j-1];
                --j;
            } while ((j > 0) && (val < A[j-1]));
            A[j] = val;
        }
    }
}
```

STL's Template Functions

- ◆ STL provides template definitions for many programming tasks
 - ◆ Use them! Do not reinvent the wheel!
 - Searching and sorting
 - ◆ `find()`, `find_if()`, `count()`, `count_if()`, `min()`, `max()`, `binary_search()`, `lower_bound()`, `upper_bound()`, `sort()`
 - Comparing
 - ◆ `equal()`
 - Rearranging and copying
 - ◆ `unique()`, `replace()`, `copy()`, `remove()`, `reverse()`, `random_shuffle()`, `merge()`
 - Iterating
 - ◆ `for_each()`

Class Templates

- ◆ Rules
 - Type template parameters
 - Value template parameters
 - ◆ Place holder for a value
 - ◆ Described using a known type and an identifier name
 - Template parameters must be used in class definition described by template
 - Implementation of member functions in header file
 - ◆ Compilers require it for now

A Generic Array Representation

- ◆ We will develop a class Array
 - Template version of IntList
 - ◆ Provides additional insight into container classes of STL

Homegrown Generic Arrays

```
Array<int> A(5, 0);           // A is five 0's
const Array<int> B(6, 1);    // B is six 1's
Array<Rational> C;          // C is ten 0/1's
A = B;
A[5] = 3;
A[B[1]] = 2;
cout << "A = " << A << endl;    // [ 1 2 1 1 1 3
]
cout << "B = " << B << endl;    // [ 1 1 1 1 1 1
]
cout << "C = " << D << endl;
    // [ 0/1 0/1 0/1 0/1 0/1 0/1 0/1 0/1 0/1 0/1
]
]
```

```

template <class T>
class Array {
public:
    Array(int n = 10, const T &val = T());
    Array(const T A[], int n);
    Array(const Array<T> &A);
    ~Array();
    int size() const {
        return NumberValues;
    }
    Array<T> & operator=(const Array<T> &A);
    const T& operator[](int i) const;
    T& operator[](int i);
private:
    int NumberValues;
    T *Values;
};

```

Optional value is default constructed

Inlined function

Auxiliary Operators

```

template <class T>
ostream& operator<<
    (ostream &sout, const Array<T> &A);

template <class T>
istream& operator>>
    (istream &sin, Array<T> &A);

```


Default Constructor

```
template <class T>
Array<T>::Array(int n, const T &val) {
    assert(n > 0);
    NumberValues = n;
    Values = new T [n];
    assert(Values);
    for (int i = 0; i < n; ++ i) {
        Values[i] = A[i];
    }
}
```

Copy Constructor

```
template <class T>
Array<T>::Array(const Array<T> &A) {
    NumberValues = A.size();
    Values = new T [A.size()];
    assert(Values);
    for (int i = 0; i < A.size(); ++i) {
        Values[i] = A[i];
    }
}
```

Destructor

```
template <class T>
  Array<T>::~~Array() {
    delete [] Values;
  }
```

Member Assignment

```
template <class T>
  Array<T>& Array<T>::operator=(const Array<T> &A) {
    if ( this != &A ) {
      if (size() != A.size()) {
        delete [] Values;
        NumberValues = A.size();
        Values = new T [A.size()];
        assert(Values);
      }
      for (int i = 0; i < A.size(); ++i) {
        Values[i] = A[i];
      }
    }
    return *this;
  }
```

Inspector for Constant Arrays

```
template <class T>
  const T& Array<T>::operator[](int i) const {
    assert((i >= 0) && (i < size()));
    return Values[i];
  }
```

Nonconstant Inspector/Mutator

```
template <class T>
  T& Array<T>::operator[](int i) {
    assert((i >= 0) && (i < size()));
    return Values[i];
  }
```

Generic Array Insertion Operator

```
template <class T>
ostream& operator<<(ostream &sout,
const Array<T> &A){
    sout << "[ ";
    for (int i = 0; i < A.size(); ++i) {
        sout << A[i] << " ";
    }
    sout << "]" ;
    return sout;
}
```

- ◆ Can be instantiated for whatever type of Array we need

Specific Array Insertion Operator

- ◆ Suppose we want a different Array insertion operator for `Array<char>` objects

```
ostream& operator<<(ostream &sout,
const Array<char> &A){
    for (int i = 0; i < A.size(); ++i) {
        sout << A[i];
    }
    return sout;
}
```

Scenario

- ◆ Manipulate list of heterogeneous objects with common base class

- Example: a list of graphical shapes to be drawn

```
// what we would like
for (int i = 0; i < n; ++i) {
    A[i].Draw();
}
```

- Need

- ◆ Draw() to be a *virtual* function

- Placeholder in the Shape class with specialized definitions in the derived class

- In C++ we can come close

Virtual Functions

- ◆ For virtual functions

- It is the type of object to which the pointer refers that determines which function is invoked

```
TriangleShape T(W, P, Red, 1);
```

```
RectangleShape R(W,P, Yellow, 3, 2);
```

```
CircleShape C(W, P, Yellow, 4);
```

```
Shape *A[3] = {&T, &R, &C};
```

```
for (int i = 0; i < 3; ++i) {
```

```
    A[i]->Draw();
}
```

← When i is 0, a TriangleShape's Draw() is used

Virtual Functions

- ◆ For virtual functions
 - It is the type of object to which the pointer refers that determines which function is invoked

```
TriangleShape T(W, P, Red, 1);
RectangleShape R(W,P, Yellow, 3, 2);
CircleShape C(W, P, Yellow, 4);

Shape *A[3] = {&T, &R, &C};

for (int i = 0; i < 3; ++i) {
    A[i]->Draw();
}
```

← When i is 1, a RectangleShape's Draw() is used

Virtual Functions

- ◆ For virtual functions
 - It is the type of object to which the pointer refers that determines which function is invoked

```
TriangleShape T(W, P, Red, 1);
RectangleShape R(W,P, Yellow, 3, 2);
CircleShape C(W, P, Yellow, 4);

Shape *A[3] = {&T, &R, &C};

for (int i = 0; i < 3; ++i) {
    A[i]->Draw();
}
```

← When i is 2, a CircleShape's Draw() is used

A Shape Class with a Virtual Draw

```
class Shape : public WindowObject {
public:
    Shape(SimpleWindow &w, const Position &p,
          const color c = Red);
    color GetColor() const;
    void SetColor(const color c);
    virtual void Draw(); // virtual function!
private:
    color Color;
};
```

Virtual Functions

- ◆ Can be invoked via either a dereferenced pointer or a reference object
 - Actual function to be invoked is determined from the *type of object that is stored at the memory location being accessed*
- ◆ Definition of the derived function overrides the definition of the base class version
- ◆ Determination of which virtual function to use cannot always be made at compile time
 - Decision is deferred by the compiler to run time
 - ◆ Introduces overhead

Pure Virtual Function

- ◆ Has no implementation
- ◆ A pure virtual function is specified in C++ by assigning the function the null address within its class definition
- ◆ A class with a pure virtual function is an *abstract base class*
 - Convenient for defining interfaces
 - Base class cannot be directly instantiated

A Shape Abstract Base Class

```
class Shape : public WindowObject {
public:
    Shape(SimpleWindow &w, const Position &p,
          const color &c = Red);
    color GetColor() const;
    void SetColor(const color &c);
    virtual void Draw() = 0; // pure virtual
                             // function!

private:
    color Color;
};
```